3M, 3M-Matic and Accueritie are tradem arbs of the 3M Company TA073 12/2000

3M-Matic[™] Case Sealers



Specifications for Box:

Regular Slotted carton (RSC)

Please request a copy of our box Specification Leaflet, TA075

Power: Electrical - 230 V, 50 Hz, 1.3 A, 240 watts Pneumatic - 5 bar min, (141 litres/min@ 21 degrees C, 1.01 bar) at 15 box es/minute

Please note: it may be possible to make machine adjustments in order to take slightly different box sizes than stated in our Product Information Sheets. For a more detailed specification, contact us.

for further details on the 800r, the further range of 3M-Matic Case Sealers, 3M's Warranties and the range of 3M Box Sealing Tapes, contact:

8001

Side Belt Drive Random Case Sealer

Dealing with assorted case sizes can be a challenge on a production line. Whether you are sealing by hand or adjusting a sealer to handle different sizes, productivity is lost.

The 800r helps you optimise productivity.
Side drive belts offer improved ability to handle narrow case widths, even those as narrow as 110mm at up to 15 cases per minute. It automatically adjusts to each case so you can seal multiple sizes with one machine without stopping for adjustments.

The 800r delivers a reliable high quality seal every time with the 3MTM AccuglideTM II Taping Head precisely applying the full range of 3M box sealing tapes.

Footprint:







